



AISIN Fully Synthetic ATF (AFW+)

PREMIUM SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

It is a high-performance, premium quality Multi-Vehicle Fluid for Automatic Transmissions. (Applicable for Slip controlled lock-up clutch). Aisin AFW+ is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications requiring SP-II, SP-III, DEXRON III, MERCON V, Allison C-4, Toyota T-III and IV. In addition, it meets the requirements of European OEM's like ZF-TE-ML-14A, Voith 55.6335, MAN 339 Type Z-1, and MB, VW, BMW 4, 5 and 6-speed automatic transmission specifications.

AFW+ is a special blend of high quality base stocks with an advanced additives system for use as a Service-Fill.

CUSTOMER BENEFITS

- Anti shudder protection
- Oxidation and thermal stability
- Provides high foam stability
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity
- Provides more stable friction property
- Use for most vehicles

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.

Specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications:-

PERFORMANCE STANDARDS

Car Maker	Vehicle Type	Specified Genuine ATF	Recommend for A/S
Toyota	FF-based 4WD vehicles	ATF Type-T	⊙
	Used for 3000cc or bigger	ATF T-II	⊙
	Flex lock up vehicles	ATF T-III	⊙
	Used for both 3000cc or more and flex lockup vehicles Type T-II and T-III were integrated	ATF Type-IV	⊙
	Toyota vehicles other than those above	ATF Dexron II-E	⊙
	Cavalier, Duet	ATF Dexron III	⊙
	Celsior, Crown (6AT), Land Cruiser 100 (5AT), Prius	ATF WS	⊙
	General AT truck and Bus (under 4T)	ATF Dexron II and T-IV	⊙
Nissan	General AT vehicles	Matic Fluid-D *	⊙
	X-Trail, Cima, Skyline 5AT, Fairlady Z	Matic Fluid-J	⊙
	Oct,2007~Skyline coupe, El Grand, Fuga 5AT	Matic Fluid-S	⊙
	Vaette	Matic Fluid-C, D / ATF M-III	⊙
	General AT truck and bus (Under 4T)	Besco ATF III	⊙
UD	General AT truck and Bus (Under 4T)	Besco ATF III	⊙
Hino	General AT truck and Bus (under 4T)	ATF Dexron II / T-IV	⊙
Mazda	General AT vehicles ATF S-1 and N-1 have been integrated into M-III	ATF M-III	⊙
	Roadstar (6AT)	ATF JWS 3317	⊙
	Premacy, Atenza, Demio, MPV, Axela	ATF M-V	⊙
	Tribute	ATF F-1	⊙
	General trucks and bus under 4t	Besco ATF III	⊙
Subaru	General AT vehicle	Subaru ATF, Subaru ATF (5AT)	⊙
	General AT vehicle	ECVT Fluid	⊙
	Traviq	Opel Original ATF 09117946	⊙
Suzuki	General AT vehicles	ATF Dexron II E	⊙
	Escudo,Alto,Cervo,Carry,Jimny, Wagon R, X-90 (3AT)	ATF 5D06	⊙
	Escudo,Cultus,Alto,Wagon R	ATF 2384K	⊙
	Eletronic Control 4AT	ATF 3314 / 3317	⊙
Isuzu	General AT vehicles	Besco ATF II/III	⊙
	General AT vehicles	Besco Dexron II-E	⊙
	General small bus & truck (under 4t)	Besco ATF III	⊙
Mitsubishi	FF vehicles and passenger car base FR vehicles (other than CVT)	Dia Queen ATF SP II/ SP II M/ SP III	⊙
	ALL FR cars which are AT	Dia Queen ATF SP III *	⊙
	Pajero io (non-turbo)	Dia Queen ATF II *	⊙
	Pajero io (turbo)	Dia Queen ATF AW	⊙
	Outlander (6AT)	Dia Queen ATF J2	⊙
	Delica Van, Truck	Dia Queen ATF SK	⊙
Honda	General AT vehicles (including S-Matic, F-Matic, 5AT)	Honda Ultra ATF/ATF Z1 *	⊙
	General AT vehicles	Honda Ultra ATF DW-1	⊙
	General AT vehicles	Honda Ultra ATF-Z1	⊙
Dahaitsu	General AT vehicle	Ammix ATF DIII Multi	⊙
	General AT vehicles	Ammix ATF D3-SP	⊙
Peodua	Kancil, Viva, Kelisa, Kenari, Kembara	ATD D-III	⊙
	Myvi, New Myvi, Nautica, Alza	P2-ATF D3 - SP	⊙

***Note : Not for use in CVT Applications**

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.

KEY PROPERTIES

Synthetic	Density, kg/liter @ 15°C	Kinematic Viscosity, mm ² /s		Pour Point (°C)	Flash Point (°C)	Brookfield Viscosity mPa·s @ -20°C	Brookfield Viscosity mPa·s @ -40°C
		@ 40°C	@ 100°C				
Fully Synthetic	0.8464	36.69	7.41	-48	226	1,341	13,800

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.