



AISIN Fully Synthetic ATF (AFW-VI)

PREMIUM SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID
Meet or exceed requirements of General Motors' DEXRON®-VI specification.

DESCRIPTION

AFW-VI is formulated with synthetic technology base oil and advanced high performance additives, and meets or exceeds the stringent requirements of General Motors' DEXRON®-VI specification. Aisin AFW-VI also meets the requirements of latest OEM specifications such as Toyota, Hyundai/Kia, MB and VW. It is also suitable for most modern 6+ speed automatic transmissions.

CUSTOMER BENEFITS

- Excellent antifoam performance
- Provides more stable friction property.
- Provides good start operation in cold climates by excellent low-temperature fluidity.
- Oxidation and thermal stability under high temperature conditions
- Provides high shear stability.
- Protect ferrous and non-ferrous materials corrosion

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.

Specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications:-

AT FLUID WIDE RANGE MEET GM DEXRON-VI (AFW-VI)

AUTOMAKER	SPECIFIED GENUINE ATF
GENERAL MOTORS (GM)	GM : DEXRON®-VI
Audi	5 HP LT71141, G 052 162-A1/A2
BMW/Mini	ATF 3+, JWS 3309 (T-IV), LA2634, ZF 5HP18FL, 5HP24, 5HP30
Chrysler/Dodge/Jeep	ATF+, +2, +3, +4, AS68RC ATF, MB 236.12
MERCEDES BENZ	MB 236.10, MB236.11, MB236.12, MB236.14
Jaguar	ATF 3403 M115, LT71141, ZF 5HP24, JLM 20292, JLM 21044, WSS-M2C9220-A1
Porsche	ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309)
Renault	Matic D2
Volkswagen (VW)	5HP (ZF 5HP 30), 5HP (18FL, 30), 5HP (19FL, 24A), TL 521 62, G 052 025 A2

***Not for use in CVT applications**

KEY PROPERTIES

Synthetic	Density, kg/liter @ 15°C	Kinematic Viscosity, mm ² /s		Pour Point (°C)	Flash Point (°C)	Brookfield Viscosity mPa·s @ -20°C	Brookfield Viscosity mPa·s @ -40°C
		@ 40°C	@ 100°C				
Fully Synthetic	0.8463	30.86	6.12	-48	220	864	12,125

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.